



INDEX FOR STAINLESS STEEL

SHEETS	46-47
PLATES	47
BARS	
Rounds	48-50
Hex	50-51
Squares	51-52
Flats	52-53
ANGLES	53
TUBING	53-54
PIPING	54
PIPE, VALVES & FITTINGS ***	

*** Pipe Chart Available in Back of this Section

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL SHEETS Type 301 Type 302 Type 304

No. 2B Finish—All Sheets
No. 3 Polish and No. 4 Polish carried in sizes up to and including 60 x 144
Some sizes carried in Type 304L

Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet
28 Ga.—(.015") .630 Lb. Sq. Ft.			18 Ga.—(.048") 2.016 Lb. Sq. Ft.			13 Ga.—(.090") 3.78 Lb. Sq. Ft.		
36x 96	15.1		30x 96	40.3		36x 96	90.7	
120	18.9		120	50.4		120	113.4	
26 Ga.—(.018") .756 Lb. Sq. Ft.			16 Ga.—(.060") 2.520 Lb. Sq. Ft.			12 Ga.—(.105") 4.410 Lb. Sq. Ft.		
30x 96	15.1		30x 96	50.4		36x 96	105.8	
120	18.9		120	63.0		120	132.3	
36x 96	18.1		36x 96	60.5		120	30.2	
120	22.7		120	75.6		48x120	40.3	
48x 96	24.2		144	96.8		22 Ga.—(.030") 1.260 Lb. Sq. Ft.		
120	30.2		56x120	94.1		36x120	37.8	
24 Ga.—(.024") 1.008 Lb. Sq. Ft.			14 Ga.—(.075") 3.150 Lb. Sq. Ft.			11 Ga.—(.120") 5.040 Lb. Sq. Ft.		
30x 96	20.2		30x 96	78.8		36x 96	120.9	
120	25.2		36x 96	75.6		120	151.2	
36x 96	24.2		120	100.8		48x 96	161.3	
120	30.2		144	121.0		120	201.6	
48x 96	32.3		54x120	113.4		144	241.9	
120	40.3		56x120	117.6		144	252.0	
22 Ga.—(.030") 1.260 Lb. Sq. Ft.			12 Ga.—(.105") 4.410 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
30x 96	25.2		36x 96	100.8		36x 96	136.1	
120	31.5		144	126.0		120	170.1	
36x 96	30.2		144	151.2		48x 96	181.4	
120	37.8		72x144	181.4		120	226.8	
144	45.4		14 Ga.—(.075") 3.150 Lb. Sq. Ft.			19 Ga.—(.043") 1.806 Lb. Sq. Ft.		
48x 96	40.3		30x120	78.8		36x120	53.0	
120	50.4		36x 96	75.6		20 Ga.—(.036") 1.512 Lb. Sq. Ft.		
20 Ga.—(.036") 1.512 Lb. Sq. Ft.			11 Ga.—(.120") 5.040 Lb. Sq. Ft.			13 Ga.—(.090") 3.780 Lb. Sq. Ft.		
30x 96	30.2		30x120	100.8		36x120	113.4	
120	37.8		144	126.0		48x120	151.2	
36x 96	36.3		144	151.2		12 Ga.—(.109") 4.5937 Lb. Sq. Ft.		
120	45.4		54x120	141.7		36x120	137.8	
42x120	52.9		60x120	157.5		48x120	183.7	
48x 96	48.4		60x120	157.5		11 Ga.—(.120") 5.040 Lb. Sq. Ft.		
120	60.5		72x120	189.0		36x120	151.2	
144	72.6		72x120	189.0		10 Ga.—(.141") 5.9062 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			14 Ga.—(.078") 3.2812 Lb. Sq. Ft.		
36x120	53.0		36x 96	136.1		36x120	98.4	
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			14 Ga.—(.078") 3.2812 Lb. Sq. Ft.		
36x120	53.0		120	170.1		48x120	131.2	
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			14 Ga.—(.078") 3.2812 Lb. Sq. Ft.		
36x120	53.0		144	211.7		11 Ga.—(.120") 5.040 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			11 Ga.—(.120") 5.040 Lb. Sq. Ft.		
36x120	53.0		60x 96	176.4		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		120	220.5		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		144	264.6		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		72x120	264.6		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		144	317.5		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		60x144	317.5		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		72x144	362.9		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
19 Ga.—(.043") 1.806 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	53.0		72x144	362.9		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		

Stainless Sheets are available in coils, which can be slit, roller leveled, and cut to length to your exact specifications.

STAINLESS STEEL SHEETS Type 316

No. 2B Finish—All Sheets
No. 3 Polish and No. 4 Polish carried in sizes up to and including 60 x 144
Some sizes carried in Type 316L

Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet
26 Ga.—(.018") .756 Lb. Sq. Ft.			20 Ga.—(.036") 1.512 Lb. Sq. Ft.			14 Ga.—(.075") 3.150 Lb. Sq. Ft.		
36x 96	18.1		36x120	45.4		36x120	94.5	
120	22.7		48x120	60.5		48x120	126.0	
48x120	30.2		18 Ga.—(.048") 2.016 Lb. Sq. Ft.			12 Ga.—(.105") 4.410 Lb. Sq. Ft.		
24 Ga.—(.024") 1.008 Lb. Sq. Ft.			16 Ga.—(.060") 2.520 Lb. Sq. Ft.			11 Ga.—(.120") 5.040 Lb. Sq. Ft.		
36x 96	24.2		36x120	75.6		36x120	151.2	
120	30.2		48x120	100.8		48x120	201.6	
48x120	40.3		60x144	151.2		10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
22 Ga.—(.030") 1.260 Lb. Sq. Ft.			14 Ga.—(.075") 3.150 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	37.8		36x120	113.4		36x120	170.1	
48x120	50.4		48x120	151.2		48x120	226.8	
22 Ga.—(.030") 1.260 Lb. Sq. Ft.			14 Ga.—(.075") 3.150 Lb. Sq. Ft.			10 Ga.—(.135") 5.670 Lb. Sq. Ft.		
36x120	37.8		36x120	113.4		48x120	226.8	
48x120	50.4		48x120	151.2		60x144	340.2	

Type 321

No. 2D Finish—All Sheets
No. 3 Polish and No. 4 Polish carried in sizes up to and including 60 x 144

Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet	Width and Estimated Length Per Sheet	Thickness	Estimated and Wt. Lbs. Per Sheet
28 Ga.—(.016") .672 Lb. Per Sq. Ft.			20 Ga.—(.036") 1.512 Lb. Sq. Ft.			13 Ga.—(.090") 3.780 Lb. Sq. Ft.		
36x120	20.2		36x120	45.4		36x120	113.4	
26 Ga.—(.01875") .7875 Lb. Sq. Ft.			19 Ga.—(.040") 1.6800 Lb. Sq. Ft.			12 Ga.—(.109") 4.5937 Lb. Sq. Ft.		
36x120	23.6		36x120	50.4		36x120	137.8	
.020" .8400 Lb. Sq. Ft.			18 Ga.—(.050") 2.1000 Lb. Sq. Ft.			11 Ga.—(.120") 5.0400 Lb. Sq. Ft.		
36x120	25.2		36x120	63.0		36x120	151.2	
24 Ga.—(.025") 1.0500 Lb. Sq. Ft.			16 Ga.—(.063") 2.6250 Lb. Sq. Ft.			10 Ga.—(.141") 5.9062 Lb. Sq. Ft.		
36x120	31.5		36x120	78.8		48x120	236.2	
22 Ga.—(.03125") 1.3125 Lb. Sq. Ft.			14 Ga.—(.078") 3.2812 Lb. Sq. Ft.			10 Ga.—(.141") 5.9062 Lb. Sq. Ft.		
36x120	39.4		36x120	98.4		48x120	236.2	
22 Ga.—(.03125") 1.3125 Lb. Sq. Ft.			14 Ga.—(.078") 3.2812 Lb. Sq. Ft.			10 Ga.—(.141") 5.9062 Lb. Sq. Ft.		
36x120	39.4		36x120	98.4		48x120	236.2	

Ordered to ASA Decimal thickness

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL SHEETS Type 347

No. 2D Finish—All Sheets
No. 3 Polish and No. 4 Polish carried in sizes up to and including 60 x 144

Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet	Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet	Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet
28 Ga.—(.015")				20 Ga.—(.036")				14 Ga.—(.075")			
.630 Lb. Sq. Ft.				1.512 Lb. Sq. Ft.				3.150 Lb. Sq. Ft.			
36x120	18.9			36x120	45.4			36x120	94.5		
26 Ga.—(.015")				19 Ga.—(.043")				13 Ga.—(.090")			
.756 Lb. Sq. Ft.				1.806 Lb. Sq. Ft.				3.780 Lb. Sq. Ft.			
36x120	22.7			36x120	54.2			36x120	113.4		
24 Ga.—(.024")				18 Ga.—(.048")				11 Ga.—(.120")			
1.008 Lb. Sq. Ft.				2.016 Lb. Sq. Ft.				5.040 Lb. Sq. Ft.			
36x120	30.2			36x120	60.5			36x120	151.2		
22 Ga.—(.030")				16 Ga.—(.060")							
1.260 Lb. Sq. Ft.				2.520 Lb. Sq. Ft.							
36x120	37.8			36x120	75.6						

Type 430

No. 2B Finish—All Sheets
No. 3 Polish and No. 4 Polish carried in sizes up to and including 60 x 144

Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet	Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet	Thickness	Width in Inches	Estimated Length	Estimated Wt. Lbs. Per Sheet
26 Ga.—(.018")				20 Ga.—(.036")				14 Ga.—(.075")			
.742 Lb. Sq. Ft.				1.483 Lb. Sq. Ft.				3.090 Lb. Sq. Ft.			
36x96	17.8			30x120	37.1			36x120	92.7		
120	22.3			36x96	35.6			48x120	123.6		
				120	44.5						
24 Ga.—(.024")				18 Ga.—(.048")				12 Ga.—(.105")			
.989 Lb. Sq. Ft.				1.978 Lb. Sq. Ft.				4.326 Lb. Sq. Ft.			
30x120	24.7			36x96	47.5			36x120	129.8		
36x96	23.2			120	59.3			48x120	173.0		
120	29.0			48x120	79.1						
48x120	39.6							11 Ga.—(.120")			
22 Ga.—(.030")				16 Ga.—(.060")				4.944 Lb. Sq. Ft.			
1.236 Lb. Sq. Ft.				2.472 Lb. Sq. Ft.				36x120	148.3		
30x120	30.9			36x120	74.2			48x120	197.8		
36x96	29.7			48x120	98.9						
120	37.1							10 Ga.—(.141")			
48x120	49.4							5.562 Lb. Sq. Ft.			
								48x120	222.5		

Stainless Sheets are available in coils, which can be slit, roller leveled, and cut to length to your exact specifications.

STAINLESS STEEL PLATES Type 302 Type 304 Type 304L Type 316 Type 316L ASTM A-240

Hot Rolled, Annealed and Pickled
All Stock Lengths not available in all Alloys.

Thickness	Size in Inches	Est. Weight, Lbs.		Thickness	Size in Inches	Est. Weight, Lbs.	
		Per Lineal Foot	Per Plate			Per Lineal Foot	Per Plate
3/16" — (.1875")				5/8" — (.625")			
8.579 Lb. Sq. Ft.				26.831 Lb. Sq. Ft.			
48x96	34.32	274.5		72x120	160.99	1609.9	
120	34.32	343.2		84x240	187.82	3756.3	
240	34.32	686.3		96x240	214.65	4293.0	
360	34.32	1029.5		360	214.65	6439.4	
60x120	42.90	429.0					
144	42.90	514.7		3/4" — (.750")			
240	42.90	857.9		32.123 Lb. Sq. Ft.			
360	42.90	1286.9		96x240	256.98	5139.7	
72x120	51.47	514.7		360	256.98	7709.5	
144	51.47	617.7					
240	51.47	1029.5		7/8" — (.875")			
360	51.47	1544.2		37.291 Lb. Sq. Ft.			
84x240	60.05	1201.1		96x240	298.33	5966.6	
360	60.05	1801.6					
96x240	68.63	1372.6		1" — (1.000")			
360	68.63	2059.0		42.665 Lb. Sq. Ft.			
				60x120	213.33	2133.3	
				96x240	341.32	6826.4	
				360	341.32	10239.6	
1/4" — (.250")							
11.162 Lb. Sq. Ft.				1 1/8" — (1.125")			
48x96	44.65	357.2		47.837 Lb. Sq. Ft.			
120	44.65	446.5		96x240	382.70	7653.9	
240	44.65	893.0					
60x240	55.81	1116.2		1 1/4" — (1.250")			
72x120	66.97	669.7		53.006 Lb. Sq. Ft.			
144	66.97	803.7		84x240	371.04	7420.8	
240	66.97	1339.4		96x240	424.05	8481.0	
360	66.97	2009.2		360	424.05	12721.4	
84x240	78.13	1562.7					
96x240	89.30	1785.9		1 1/2" — (1.500")			
360	89.30	2344.0		63.331 Lb. Sq. Ft.			
				84x240	443.32	8866.3	
5/16" — (.3125")				96x240	506.65	10133.0	
13.746 Lb. Sq. Ft.				360	506.65	15199.4	
72x240	82.48	1649.5					
84x240	96.22	1924.4		1 3/4" — (1.750")			
96x240	109.97	2199.4		73.670 Lb. Sq. Ft.			
360	109.97	3299.0		84x240	515.69	10313.8	
				96x240	589.36	11787.2	
				360	589.36	17680.8	
3/8" — (.375")							
16.496 Lb. Sq. Ft.				2" — (2.000")			
48x240	65.98	1319.7		84.009 Lb. Sq. Ft.			
72x240	98.98	1979.5		84x240	588.06	11761.3	
360	98.98	2962.3		96x120	672.07	6720.7	
84x240	115.47	2309.4		240	672.07	13441.4	
96x240	131.97	2639.4					
360	131.97	3959.0		2 1/4" — (2.250")			
				94.781 Lb. Sq. Ft.			
1/2" — (.500")				96x240	758.25	15165.0	
21.663 Lb. Sq. Ft.							
72x240	129.98	2599.6		2 1/2" — (2.500")			
84x240	151.64	3032.8		105.120 Lb. Sq. Ft.			
96x240	173.30	3466.1		84x120	735.84	7358.4	
360	173.30	5199.1		96x240	840.96	16819.2	
5/16" — (.5625")				3" — (3.000")			
24.247 Lb. Sq. Ft.				126.302 Lb. Sq. Ft.			
84x240	169.73	3394.6		84x240	884.11	17682.3	
96x240	193.98	3879.5		96x240	1010.42	20208.3	

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS ROUNDS Type 303

Some sizes carried in Type 303Se

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar
1/16	.010	.12	1	2.670	32.04	5	66.76	801.1									
3/32	.023	.28	1 1/16	3.014	36.17	5 1/4	73.60	883.2									
1/8	.042	.50	1 1/8	3.379	40.55	5 1/2	80.78	969.4									
5/32	.065	.78	1 3/16	3.766	45.19	5 3/4	88.29	1059									
3/16	.094	1.13	1 1/4	4.173	50.08	6	96.13	1154									
7/32	.128	1.54	1 5/16	4.600	55.20	6 1/4	104.3	1252									
1/4	.167	2.00	1 3/8	5.049	60.59	6 3/4	121.7	1460									
9/32	.211	2.53	1 7/16	5.518	66.22	7 1/2	150.2	1802									
5/16	.261	3.13	1 1/2	6.008	72.10	8	170.9	2051									
11/32	.316	3.79	1 5/8	6.520	78.24												
3/8	.376	4.51	1 3/4	7.051	84.61												
13/32	.441	5.29	1 11/16	7.604	91.25												
7/16	.511	6.13	1 3/4	8.178	98.14												
15/32	.587	7.04	1 13/16	8.773	105.3												
1/2	.668	8.02	1 7/8	9.388	112.7												
17/32	.754	9.05	1 15/16	10.02	120.2												
9/16	.845	10.14															
19/32	.941	11.29	2	10.68	128.2												
5/8	1.043	12.52	2 1/8	12.06	144.7												
21/32	1.150	13.80	2 1/4	12.78	153.4												
11/16	1.262	15.14	2 1/2	13.52	162.2	1	2.670	32.04									
23/32	1.379	16.55	2 3/8	15.06	180.7	1 1/8	3.379	40.55									
3/4	1.502	18.02	2 1/2	15.87	190.4	1 1/4	3.766	45.19									
25/32	1.630	19.56	2 5/8	16.69	200.3	1 1/2	4.173	50.08									
13/16	1.763	21.16	2 3/4	18.40	220.8	1 3/8	5.049	60.59									
27/32	1.901	22.81	2 7/8	20.20	242.4	1 1/2	5.518	66.22									
7/8	2.044	24.53	2 7/8	22.07	264.8	1 5/8	6.008	72.10									
29/32	2.193	26.32				1 3/4	6.520	78.24									
15/16	2.347	28.16	3	24.03	288.4	1 7/8	7.051	84.61									
31/32	2.506	30.07	3 1/4	28.21	338.5	1 7/8	8.178	98.14									
			3 1/2	32.71	392.5	2	10.68	128.2									
			3 3/4	37.55	450.6	2 1/4	13.52	162.2									
						3	24.03	288.4									
			4	42.73	512.8												
			4 1/4	48.23	578.8												
			4 1/2	54.08	649.0												
			4 3/4	60.25	723.0												

ROUNDS Type 309

Hot Rolled and Annealed
Stock Lengths, 22' to 24'

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
in	Per Foot	24 Ft. Bar	in	Per Foot	24 Ft. Bar	in	Per Foot	24 Ft. Bar	in	Per Foot	24 Ft. Bar	in	Per Foot	24 Ft. Bar	in	Per Foot	24 Ft. Bar
1/2	.668	16.03	3/4	1.502	36.05	1	2.670	64.08									
5/8	1.043	25.03	7/8	2.044	49.06												

STAINLESS STEEL BARS ROUNDS Type 310

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar
1/4	.167	2.00	1	2.670	32.04	2 3/8	15.06	180.7									
3/8	.376	4.51	1 1/4	4.173	50.08	2 1/2	16.69	200.3									
1/2	.668	8.02	1 1/2	6.008	72.10	3 1/4	28.21	338.5									
5/8	1.043	12.52	1 3/4	8.178	98.14	3 3/4	37.55	450.6									
3/4	1.502	18.02	2	10.68	128.2	4	42.73	512.8									
			2 1/4	13.52	162.2												

ROUNDS Type 316

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar
1/8	.042	.50	1 7/16	5.518	66.22	3	24.03	288.4									
3/16	.094	1.13	1 1/2	6.008	72.10	3 3/8	26.08	313.0									
1/4	.167	2.00	1 3/4	7.051	84.61	3 1/2	28.21	338.5									
5/16	.261	3.13	1 11/16	7.604	91.25	3 3/4	30.42	365.0									
3/8	.376	4.51	1 3/4	8.178	98.14	3 1/2	32.71	392.5									
7/16	.511	6.13	1 7/8	9.388	112.7												
1/2	.668	8.02	1 15/16	10.02	120.2												
9/16	.845	10.14															
19/32	.941	11.29	2	10.68	128.2												
5/8	1.043	12.52	2 1/8	12.06	144.7												
21/32	1.150	13.80	2 1/4	12.78	153.4												
11/16	1.262	15.14	2 1/2	13.52	162.2												
23/32	1.379	16.55	2 3/8	15.06	180.7												
3/4	1.502	18.02	2 1/2	15.87	190.4												
25/32	1.630	19.56	2 5/8	16.69	200.3												
13/16	1.763	21.16	2 3/4	18.40	220.8												
27/32	1.901	22.81	2 7/8	20.20	242.4												
7/8	2.044	24.53	2 7/8	22.07	264.8												
29/32	2.193	26.32															
15/16	2.347	28.16	3	24.03	288.4												
31/32	2.506	30.07	3 1/4	28.21	338.5												
			3 1/2	32.71	392.5												
			3 3/4	37.55	450.6												
			4	42.73	512.8												
			4 1/4	48.23	578.8												
			4 1/2	54.08	649.0												
			4 3/4	60.25	723.0												

ROUNDS Type 321

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar	in	Per Foot	12 Ft. Bar
1/8	.042	.50	1 3/8	5.049	60.59	3 3/8	30.42	365.0									
3/16	.094	1.13	1 1/2	6.008	72.10	3 1/2	32.71	392.5									
1/4	.167	2.00	1 3/4	7.051	84.61	3 5/8	35.09	421.1									
5/16	.261	3.13				3 3/4	37.55	450.6									
3/8	.376	4.51															
7/16	.511	6.13															
1/2	.668	8.02															
9/16	.845	10.14															
5/8	1.043	12.52															
3/4	1.502	18.02															
7/8	2.044	24.53															
15/16	2.347	28.16						</									

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS ROUNDS Type 347

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
1/8	.042	.50	1/4	4.173	50.08	3	24.03	288.4	3/16	.094	1.13	1/2	6.008	72.10	3 3/4	28.21	338.5
1/4	.167	2.00	5/16	6.520	78.24	4	42.73	512.8	7/16	.261	3.13	3/8	8.773	105.3	4 1/2	37.55	450.6
5/16	.376	4.51	1/2	9.388	112.7	5 1/4	48.23	578.8	1 1/2	.511	6.13	1/2	15.87	190.4	5 1/2	60.25	723.0
11/32	.316	3.79	3/8	12.78	153.4	6	66.76	801.1	1 3/4	.587	7.04	2 1/8	15.87	190.4	6 1/2	80.78	969.4
3/8	.376	4.51	2 3/16	15.87	190.4	5 3/4	73.60	883.2	1 7/8	.754	9.05	2 1/4	18.40	220.8	7	88.29	1059
13/32	.441	5.29	2 1/2	18.40	220.8	6 3/4	80.78	969.4	2	.845	10.14	2 3/8	20.20	242.4	7 1/2	96.13	1154
7/16	.511	6.13	Hot Rolled, Annealed and Pickled			7	104.3	1253	2 1/2	1.043	12.52	3	24.03	288.4	8	170.9	2051
15/32	.587	7.04	1 3/4	8.178	98.14	7 1/2	112.8	1354	3 1/8	1.262	15.14	3 1/2	32.71	392.5			
1/2	.668	8.02	2	10.68	128.2	8	170.9	2051	3 1/4	1.502	18.02	4	42.73	512.8			
17/32	.754	9.05	2 1/8	12.06	144.7				3 3/8	1.763	21.16						
9/16	.845	10.14	2 1/4	13.52	162.2				7/8	2.044	24.53						
5/8	1.043	12.52	2 3/8	15.06	180.7				1	2.670	32.04						
11/16	1.262	15.14	2 1/2	16.69	200.3				1 1/16	3.014	36.17						
3/4	1.502	18.02	2 3/4	20.20	242.4				1 1/8	3.379	40.55						
13/16	1.763	21.16															
7/8	2.044	24.53															

ROUNDS Type 410

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
1/4	.167	2.00	7/8	2.044	24.53	1 3/4	8.178	98.14	3/8	.376	4.51	1 7/8	9.388	112.7	2	10.68	128.2
5/16	.261	3.13	15/16	2.347	28.16	2	10.68	128.2	7/16	.511	6.13	2 1/4	13.52	162.2	3	24.03	288.4
3/8	.376	4.51	1	2.670	32.04	2 1/2	16.69	200.3	1/2	.668	8.02	3 1/8	1.763	21.16	3 1/2	32.71	392.5
7/16	.511	6.13	1 1/8	3.379	40.55	3	24.03	288.4	5/8	.845	10.14	3 1/4	1.502	18.02			
1/2	.668	8.02	1 1/4	4.173	50.08	3 1/2	32.71	392.5	9/16	1.043	12.52	3 3/8	1.763	21.16			
5/8	1.043	12.52	1 1/2	6.008	72.10				11/16	1.262	15.14						
11/16	1.262	15.14	1 3/8	5.049	60.59				3/4	1.502	18.02						
3/4	1.502	18.02	1 3/4	6.008	72.10				13/16	1.763	21.16						
13/16	1.763	21.16	1 7/8	7.051	84.61												
			2	10.68	128.2												
			2 1/8	12.06	144.7												
			2 1/4	13.52	162.2												
			2 3/8	15.06	180.7												
			2 1/2	16.69	200.3												
			2 3/4	20.20	242.4												

Hot Rolled and Heat Treated
Stock Lengths, 22' to 24'

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	24 Ft. Bar		Per Foot	24 Ft. Bar		Per Foot	24 Ft. Bar		Per Foot	24 Ft. Bar		Per Foot	24 Ft. Bar		Per Foot	24 Ft. Bar	
Brinell 235-277			2	10.68	256.3	4	42.73	1026	Hot Rolled, Annealed and Pickled								
Hardenable to Brinell 401			2 1/4	13.52	324.5	4 1/4	48.23	1158	Max. Brinell 202								
1 1/8	3.379	81.10	2 1/2	16.69	400.6	4 1/2	54.08	1298									
1 3/16	3.474	83.38	2 3/4	20.20	484.8	4 3/4	60.25	1446									
1 1/2	5.049	121.2	3	24.03	576.7	5 1/4	73.60	1766									
1 5/8	6.008	144.2	3 1/4	28.21	677.0	5 1/2	80.78	1939									
1 7/8	7.051	169.2	3 1/2	32.71	785.0	6 1/4	104.3	2503									
1 3/4	8.178	196.3	3 3/4	37.55	901.2												
1 7/8	9.388	225.3															

*Ground Finish

STAINLESS STEEL BARS ROUNDS Type 416

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
3/32	.023	.28	13/16	1.763	21.16	2	10.68	128.2	1/8	.042	.50	2 1/16	11.36	136.3	3/8	.376	4.51
1/8	.042	.50	27/32	1.901	22.81	2 1/8	12.06	144.7	5/32	.065	.78	2 1/4	12.78	153.4	7/16	.511	6.13
1/4	.167	2.00	7/8	2.044	24.53	2 3/8	13.52	162.2	3/16	.094	1.13	2 1/2	13.52	162.2	9/16	.845	10.14
5/16	.261	3.13	29/32	2.193	26.32	2 3/4	14.28	171.4	11/32	.316	3.79	2 5/8	14.28	171.4	1	2.670	32.04
3/8	.376	4.51	15/16	2.347	28.16	3	24.03	288.4	1/2	.668	8.02	2 7/8	15.06	180.7	1 1/16	3.014	36.17
7/16	.511	6.13	31/32	2.506	30.07	3 1/8	24.03	288.4	5/8	.845	10.14	3 1/16	15.87	190.4	1 1/8	3.379	40.55
1/2	.668	8.02				3 1/4	24.03	288.4	9/16	1.043	12.52	3 1/8	16.69	200.3	1 1/4	4.173	50.08
5/8	1.043	12.52				3 3/8	24.03	288.4	1	2.670	32.04	3 1/2	18.40	220.8	1 1/2	6.008	72.10
11/16	1.262	15.14				3 3/4	24.03	288.4	1 1/8	3.379	40.55	4	42.73	512.8	1 3/4	7.051	84.61
3/4	1.502	18.02				4	42.73	512.8	1 1/16	3.014	36.17	4 1/2	54.08	649.0	1 7/8	8.178	98.14
13/16	1.763	21.16							1 1/4	4.173	50.08	4 3/4	60.25	723.0	2	10.68	128.2
7/8	2.044	24.53							1 1/2	6.008	72.10				2 1/8	12.06	144.7
1	2.670	32.04							1 3/4	7.051	84.61				2 1/4	13.52	162.2
1 1/16	3.014	36.17							1 5/8	8.178	98.14				2 3/8	15.06	180.7
1 1/8	3.379	40.55							1 7/8	9.388	112.7				2 1/2	16.69	200.3
									2	10.68	128.2				2 3/4	18.40	220.8
									2 1/16	11.36	136.3				3	24.03	288.4
									2 1/8	12.06	144.7				3 1/8	24.03	288.4
									2 3/8	13.52	162.2				3 1/4	28.21	338.5
									2 1/2	14.28	171.4				3 3/8	30.42	365.0
									2 5/8	15.06	180.7				3 1/2	32.71	392.5
									3	16.69	200.3				3 3/4	37.55	450.6
									3 1/8	18.40	220.8						
									3 1/4	20.20	242.4						
									3 3/8	22.07	264.8						
									3 1/2	24.03	288.4						
									3 3/4	26.08	313.0						
									4	28.21	338.5						
									4 1/2	30.42	365.0						
									4 3/4	32.71	392.5						
									5	37.55	450.6						
									5 1/4	42.73	512.8						
									5 1/2	48.23	578.8						
									6	54.08	649.0						
									6 1/2	60.25	723.0						
									7	66.76	801.1						
									7 1/2	73.60	883.2						
									8	80.78	969.4						

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS ROUNDS Type 431

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
3/16	.094	1.13	1	2.670	32.04	2 3/8	15.06	180.7									
1/4	.167	2.00	1 1/8	3.379	40.55	2 1/2	16.69	200.3									
5/16	.261	3.13	1 1/4	4.173	50.08	2 3/8	18.40	220.8									
3/8	.376	4.51	1 3/8	5.049	60.59	2 1/2	20.20	242.4									
7/16	.511	6.13	1 1/2	6.008	72.10	3	24.03	288.4									
1/2	.668	8.02	1 5/8	7.051	84.61	3 1/4	28.21	338.5									
9/16	.845	10.14	1 3/4	8.178	98.14	3 1/2	32.71	392.5									
5/8	1.043	12.52	Hot Rolled, Annealed and Pickled						3 3/4	37.55	450.6						
11/16	1.262	15.14	1 7/8	7.051	84.61	4	42.73	512.8									
3/4	1.502	18.02	1 3/4	8.178	98.14	4 1/2	54.08	649.0									
13/16	1.763	21.16	1 7/8	9.388	112.7	5	66.76	801.1									
7/8	2.044	24.53	2	10.68	128.2	5 1/2	80.78	969.4									
15/16	2.347	28.16	2 1/8	12.06	144.7	6	96.13	1154									
			2 1/4	13.52	162.2												

ROUNDS Type 440-A Type 440-C

Under 1/2", Cold Drawn Finish
1/2" and over, Ground Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
1/8	.042	.50	1	2.670	32.04	1 3/8	7.051	84.61									
5/32	.065	.78	1 1/16	3.014	36.17	1 3/4	8.178	98.14									
3/16	.094	1.13	1 1/8	3.379	40.55	1 7/8	9.388	112.7									
7/32	.128	1.54	1 1/4	4.173	50.08	2	10.68	128.2									
1/4	.167	2.00	1 3/8	4.600	55.20	2 1/8	12.06	144.7									
9/32	.211	2.53	1 3/8	5.049	60.59	2 3/16	12.78	153.4									
5/16	.261	3.13	1 1/2	5.518	66.22	2 1/4	13.52	162.2									
11/32	.316	3.79	1 1/2	6.008	72.10	2 1/2	15.06	180.7									
3/8	.376	4.51	1 5/8	6.520	78.24	2 3/8	16.69	200.3									
13/32	.441	5.29	1 3/4	7.051	84.61	2 3/8	18.40	220.8									
7/16	.511	6.13	1 3/4	8.178	98.14	2 1/2	20.20	242.4									
15/32	.587	7.04	1 7/8	9.388	112.7	3	24.03	288.4									
1/2	.668	8.02	2	10.68	128.2	3 1/4	28.21	338.5									
9/16	.845	10.14	2 1/2	16.69	200.3	3 1/2	32.71	392.5									
5/8	1.043	12.52	Hot Rolled, Annealed and Pickled						3 3/4	37.55	450.6						
11/16	1.262	15.14	1 3/8	3.379	40.55	4	42.73	512.8									
3/4	1.502	18.02	1 3/8	5.049	60.59	4 1/2	54.08	649.0									
13/16	1.763	21.16															
7/8	2.044	24.53															
15/16	2.347	28.16															

ROUNDS Type 501

Hot Rolled, Heat Treated, 1100° Minimum Draw
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
1/2	.668	8.02	1	2.670	32.04	1 1/2	6.008	72.10									
5/8	1.043	12.52	1 1/8	3.379	40.55	1 3/4	8.178	98.14									
3/4	1.502	18.02	1 1/4	4.173	50.08	1 7/8	9.388	112.7									
7/8	2.044	24.53	1 3/8	5.049	60.59	2	10.68	128.2									

STAINLESS STEEL BARS ROUNDS Type 17-4 PH

Condition A
Annealed and Ground
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
1/8	.042	.50	1	2.670	32.04	2 3/8	15.06	180.7									
3/16	.094	1.13	1 1/16	3.014	36.17	2 1/2	16.69	200.3									
1/4	.167	2.00	1 1/8	3.379	40.55	2 3/8	18.40	220.8									
9/32	.211	2.53	1 3/16	3.766	45.19	2 1/2	20.20	242.4									
5/16	.261	3.13	1 1/4	4.173	50.08	2 3/8	22.07	264.8									
11/32	.316	3.79	1 3/8	5.049	60.59	3	24.03	288.4									
3/8	.376	4.51	1 1/2	6.008	72.10	3 1/4	28.21	338.5									
13/32	.441	5.29	1 5/8	7.051	84.61	3 1/2	32.71	392.5									
7/16	.511	6.13	1 3/4	8.178	98.14	3 3/4	37.55	450.6									
15/32	.587	7.04	1 7/8	9.388	112.7	4	42.73	512.8									
1/2	.668	8.02	1 7/8	10.02	120.2	4 1/4	48.23	578.8									
9/16	.845	10.14	2	10.68	128.2	4 3/4	60.25	723.0									
5/8	1.043	12.52	2 1/8	12.06	144.7	5	66.76	801.1									
11/16	1.262	15.14	2 1/4	13.52	162.2	5 1/2	80.78	969.4									
3/4	1.502	18.02															
13/16	1.763	21.16															
7/8	2.044	24.53															
15/16	2.347	28.16															

HEXAGONS Type 303

Cold Drawn Finish
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
3/16	.104	1.25	1	2.945	35.34	2	11.78	141.4									
1/4	.184	2.21	1 1/16	3.324	39.89	2 1/4	14.91	178.9									
5/16	.288	3.46	1 1/8	3.727	44.72	2 3/8	16.61	199.3									
3/8	.414	4.97	1 1/4	4.152	49.82	2 1/2	18.40	220.8									
7/16	.564	6.77	1 1/4	4.601	55.21	2 3/8	20.29	243.5									
1/2	.736	8.83	1 1/2	5.072	60.86	2 1/2	22.27	267.2									
9/16	.932	11.18	1 3/8	5.567	66.80	2 3/8	23.29	279.5									
5/8	1.150	13.80	1 3/8	6.085	73.02	2 3/8	24.34	292.1									
11/16	1.392	16.70	1 1/2	6.625	79.50	3	26.50	318.0									
3/4	1.656	19.87	1 5/8	7.775	93.30												
13/16	1.944	23.33	1 3/4	9.018	108.2												
7/8	2.254	27.05	1 7/8	10.35	124.2												
15/16	2.588	31.06	1 5/8	11.05	132.6												

HEXAGONS Type 316

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
3/8	.414	4.97	1	2.945	35.34	1 3/8	7.775	93.30									
7/16	.564	6.77	1 1/8	3.565	42.78	1 3/4	9.018	108.2									
1/2	.736	8.83	1 1/4	4.601	55.21	1 7/8	10.35	124.2									
5/8	1.150	13.80	1 1/2	4.852	58.22												
3/4	1.656	19.87	1 3/8	5.567	66.80	2	11.78	141.4									
7/8	2.156	25.87	1 1/2	6.337	76.04												

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS HEXAGONS Type 321

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.184	2.21	1/4	1.656	19.87	3/4	5.567	66.80	1 1/2	6.625	79.50	1 1/2	7.775	93.30	1 3/4	9.018	108.2	
.288	3.46	5/16	2.254	27.05	7/8	10.35	124.2	1 3/8	11.78	141.4	2						
.414	4.97	3/8	2.588	31.06	1 5/16												
.564	6.77	7/16															
.736	8.83	1/2															
.932	11.18	9/16															
1.150	13.80	5/8															
1.392	16.70	1 1/16															

STAINLESS STEEL BARS HEXAGONS Type 17-4 PH

Condition A
Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.736	8.83	1/2	2.945	35.34	1	4.601	55.21	1 1/4	5.567	66.80	1 3/8	6.625	79.50	1 1/2			
1.150	13.80	5/8	3.727	44.72	1 1/8												
1.656	19.87	3/4															
2.254	27.05	7/8															

HEXAGONS Type 347

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.414	4.97	3/8	2.945	35.34	1	11.78	141.4	2									
.564	6.77	7/16	3.727	44.72	1 1/8	13.30	159.6	2 1/8									
.736	8.83	1/2	4.152	49.82	1 3/16	14.09	169.1	2 3/16									
.932	11.18	9/16	4.601	55.21	1 1/4	14.91	178.9	2 1/2									
1.150	13.80	5/8	5.567	66.80	1 3/8	16.61	199.3	2 3/8									
1.392	16.70	1 1/16	6.625	79.50	1 1/2	18.40	220.8	2 1/2									
1.656	19.87	3/4	7.775	93.30	1 5/8	20.29	243.5	2 5/8									
1.944	23.33	13/16	8.385	100.6	1 3/4	22.27	267.2	2 3/4									
2.254	27.05	7/8	9.018	108.2	1 7/8	23.29	279.5	2 13/16									
2.588	31.06	1 5/16	10.35	124.2	1 15/16												
			11.05	132.6													

HEXAGONS Type 416

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.184	2.21	1/4	1.656	19.87	3/4	4.601	55.21	1 1/4	5.567	66.80	1 3/8	6.625	79.50	1 1/2	7.775	93.30	
.288	3.46	5/16	2.254	27.05	7/8	6.625	79.50	1 1/2	7.775	93.30	1 3/4	9.018	108.2	1 3/8	10.35	124.2	
.414	4.97	3/8	2.588	31.06	1 5/16												
.564	6.77	7/16															
.736	8.83	1/2															
.932	11.18	9/16															
1.150	13.80	5/8															
1.392	16.70	1 1/16															

HEXAGONS Type 431

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.414	4.97	3/8	1.656	19.87	3/4	2.945	35.34	1	3.324	39.89	1 1/16	3.727	44.72	1 1/8	4.601	55.21	
.564	6.77	7/16	1.944	23.33	13/16	5.567	66.80	1 1/2	6.625	79.50	1 3/8	7.775	93.30	1 1/4	9.018	108.2	
.736	8.83	1/2	2.254	27.05	7/8	10.35	124.2	1 3/8	11.78	141.4	2						
.932	11.18	9/16	2.588	31.06	1 5/16												
1.150	13.80	5/8															
1.392	16.70	1 1/16															

SQUARES Type 303

Some sizes carried in Type 303S and Type 303E
Condition A—Annealed
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.053	.64	1/8	3.400	40.80	1	4.303	51.64	1 1/8	5.313	63.76	1 1/4	6.428	77.14	1 3/8	7.650	91.80	
.120	1.44	3/16	4.601	55.21	1 1/4	5.567	66.80	1 1/2	6.625	79.50	1 3/4	7.775	93.30	1 3/8	9.018	108.2	
.213	2.56	1/4	8.385	100.6	1 3/4	9.018	108.2	1 7/8	10.35	124.2	1 15/16						
.332	3.98	5/16	11.78	141.4	2												
.478	5.74	3/8															
.651	7.81	7/16															
.850	10.20	1/2															
1.328	15.94	5/8															
1.913	22.96	3/4															
2.603	31.24	7/8															

Condition B—High Tensile
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.213	2.56	1/4	1.328	15.94	5/8	3.400	40.80	1	4.303	51.64	1 1/8	5.313	63.76	1 1/4	6.428	77.14	
.478	5.74	3/8	1.913	22.96	3/4	7.650	91.80	1 3/8	9.018	108.2	1 7/8	10.35	124.2	1 15/16			
.850	10.20	1/2	2.603	31.24	7/8												

SQUARES Type 316

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.			Size in Inches			Est. Weight, Lbs.		
Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
.213	2.56	1/4	.850	10.20	1/2	3.400	40.80	1	4.303	51.64	1 1/8	5.313	63.76	1 1/4	6.428	77.14	
.332	3.98	5/16	1.328	15.94	5/8	7.650	91.80	1 3/8	9.018	108.2	1 7/8	10.35	124.2	1 15/16			
.478	5.74	3/8	1.913	22.96	3/4												
.651	7.81	7/16															

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS SQUARES Type 416

Annealed and Cold Drawn
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar	
3/16	.120	1.44	3/4	1.913	22.96	Hot Rolled, Annealed and Pickled	1 1/8	8.978	107.7
1/4	.213	2.56	7/8	2.603	31.24		2	13.60	163.2
5/16	.332	3.98	1 1/8	2.988	35.86		2 1/2	21.25	255.0
3/8	.478	5.74	1	3.400	40.80		3	30.60	367.2
7/16	.651	7.81	1 1/4	5.313	63.76				
1/2	.850	10.20	1 3/8	6.428	77.14				
5/8	1.328	15.94	1 1/2	7.650	91.80				

SQUARES Type 17-4 PH

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/2	.850	10.20	1	3.400	40.80	2	13.60	163.2
3/4	1.913	22.96	1 1/4	5.313	63.76			
			1 1/2	7.650	91.80			

FLATS Type 302 Type 304

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/8 x 1/2	.213	2.56	3/8 x 1/2	.638	7.66	3/4 x 1	2.550	30.60
1/8 x 3/4	.319	3.83	3/8 x 3/4	.956	11.47	1 1/4	3.188	38.26
1/8 x 1	.425	5.10	1	1.275	15.30	1 1/2	3.825	45.90
1/8 x 1 1/4	.531	6.37	1 1/4	1.594	19.13	1 3/4	4.463	53.56
1/8 x 1 1/2	.638	7.66	1 1/2	1.913	22.96	2	5.100	61.20
1/8 x 2	.850	10.20	2	2.550	30.60	2 1/2	6.375	76.50
1/8 x 2 1/2	1.063	12.76	2 1/2	3.188	38.26	3	7.650	91.80
1/8 x 3	1.275	15.30	3	3.825	45.90	3 1/2	8.925	107.1
1/8 x 3 1/2	1.488	17.86	3 1/2	4.463	53.56	4	10.20	122.4
			4	5.100	61.20	6	15.30	183.6
3/16 x 3/4	.478	5.74	4 1/2	5.738	68.86	1 x 1 1/4	4.250	51.00
1/4	.638	7.66	5	6.375	76.50	1 1/2	5.100	61.20
1/4 x 1/4	.797	9.56	1/2 x 1	1.700	20.40	2	6.800	81.60
1/4 x 1 1/2	.956	11.47	1 1/4	2.125	25.50	3	10.20	122.4
1/4 x 2	1.275	15.30	1 1/2	2.550	30.60	3 1/2	11.90	142.8
1/4 x 2 1/2	1.594	19.13	1 3/4	2.975	35.70	4	13.60	163.2
1/4 x 3	1.913	22.96	2	3.400	40.80	6	20.40	244.8
1/4 x 4	2.550	30.60	2 1/2	4.250	51.00	3	5.100	61.20
			3	5.100	61.20	1 1/4 x 2	8.500	102.0
1/4 x 1/2	.425	5.10	3 1/2	5.950	71.40	2 1/2	10.63	127.6
1/4 x 3/4	.638	7.66	4	6.800	81.60	3	12.75	153.0
1/4 x 1	.850	10.20	4 1/2	7.650	91.80	4	17.00	204.0
1/4 x 1 1/4	1.063	12.76	5	8.500	102.0			
1/4 x 1 1/2	1.275	15.30	6	10.20	122.4	1 1/2 x 1 1/4	8.925	107.1
1/4 x 2	1.700	20.40	1/8 x 3/4	1.594	19.13	3	15.30	183.6
1/4 x 2 1/2	2.125	25.50	1	1.700	20.40	4	20.40	244.8
1/4 x 3	2.550	30.60	1 1/2	3.188	38.26	2 x 3	20.40	244.8
1/4 x 3 1/2	2.975	35.70	2	4.250	51.00	4	27.20	326.4
1/4 x 4	3.400	40.80	2 1/2	5.313	63.76			
1/4 x 4 1/2	3.825	45.90	3	6.375	76.50	3 x 4	40.80	489.6

STAINLESS STEEL BARS FLATS Type 316

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/8 x 1	.425	5.10	3/8 x 1	1.275	15.30	3/4 x 1	2.550	30.60
1 1/2	.638	7.66	1 1/2	1.913	22.96	1 1/2	3.825	45.90
2	.850	10.20	2	2.550	30.60	2	5.100	61.20
3	1.275	15.30	3	3.825	45.90	3	7.650	91.80
			3/16 x 1	.638	7.66	1/2 x 1	1.700	20.40
			1 1/2	.956	11.47	1 1/2	2.550	30.60
			2	1.275	15.30	2	3.400	40.80
						2 1/2	4.250	51.00
1/4 x 1	.850	10.20				3	5.100	61.20
1 1/2	1.275	15.30				4	6.800	81.60
2	1.700	20.40						
3	2.550	30.60						
4	3.400	40.80						

FLATS Type 321

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/4 x 1/2	.425	5.10	1/2 x 3/4	1.275	15.30	1 x 1 1/4	4.250	51.00
1/4 x 3/4	.638	7.66	1	1.700	20.40	1 1/2	5.100	61.20
1/4 x 1	.850	10.20	1 1/4	2.125	25.50	1 3/4	5.950	71.40
1/4 x 1 1/4	1.063	12.76	1 1/2	2.550	30.60	2 1/2	8.500	102.0
1/4 x 1 1/2	1.275	15.30	1 3/4	2.975	35.70	3	10.20	122.4
1/4 x 1 3/4	1.488	17.86	2	3.400	40.80	4	13.60	163.2
1/4 x 2	1.700	20.40	2 1/2	4.250	51.00	6	20.40	244.8
1/4 x 2 1/2	2.125	25.50	3	5.100	61.20			
1/4 x 3	2.550	30.60	4	6.800	81.60	1 1/4 x 2	8.500	102.0
1/4 x 4	3.400	40.80	6	10.20	122.4	2 1/2	10.63	127.6
1/4 x 6	5.100	61.20				3	12.75	153.0
						4	17.00	204.0
3/8 x 1/2	.638	7.66	3/8 x 1	2.125	25.50			
3/8 x 3/4	.956	11.47	2	4.250	51.00	1 1/2 x 2	10.20	122.4
1	1.275	15.30	3/4 x 1	2.550	30.60	3	15.30	183.6
1 1/2	1.913	22.96	1 1/4	3.188	38.26			
2	2.550	30.60	1 1/2	3.825	45.90	2 x 3	20.40	244.8
2 1/2	3.188	38.26	1 3/4	4.463	53.56	4	27.20	326.4
3	3.825	45.90	2	5.100	61.20			
4	5.100	61.20	2 1/2	6.375	76.50	3 x 4	40.80	489.6
			3	7.650	91.80			
			4	10.20	122.4			
			6	15.30	183.6			

FLATS Type 347

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/4 x 1	.850	10.20	1/2 x 1	1.700	20.40	3/4 x 1	2.550	30.60
1 1/2	1.275	15.30	1 1/2	2.550	30.60	2	5.100	61.20
2	1.700	20.40	2	3.400	40.80	1 x 1 1/2	5.100	61.20
			3	5.100	61.20	2	6.800	81.60

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL BARS FLATS Type 17-4 PH

Hot Rolled, Annealed and Pickled
Stock Length, 12' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar		Per Foot	12 Ft. Bar
1/4 x 1	.850	10.20	1/2 x 4	6.800	81.60	1 x 3	10.20	122.4
1 1/2	1.275	15.30				4	13.60	163.2
2	1.700	20.40	3/4 x 1	2.550	30.60			
3	2.550	30.60	1 1/2	3.825	45.90	1 1/2 x 2	10.20	122.4
4	3.400	40.80	2	5.100	61.20	3	15.30	183.6
			3	7.650	91.80	4	20.40	244.8
1/2 x 1	1.700	20.40	4	10.20	122.4			
1 1/2	2.550	30.60				2 x 2 1/2	17.00	204.0
2	3.400	40.80	1 x 1 1/2	5.100	61.20	3	20.40	244.8
3	5.100	61.20	2	6.800	81.60	4	27.20	326.4

STAINLESS STEEL ANGLES Type 302 Type 304

Hot Rolled, Annealed and Pickled
Stock Length, 20' Random

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	20 Ft. Length		Per Foot	20 Ft. Length
3/4 x 3/4 x 1/8	.59	11.8	1 1/4 x 1 1/4 x 1/4	2.77	55.4
1 x 1 x 1/8	.80	16.0			
	1.16	23.2	2 x 2 x 1/8	1.65	33.0
	1.49	29.8		3/16	2.44
				1/4	3.19
1 1/4 x 1 1/4 x 1/8	1.01	20.2			
	1.48	29.6	2 1/2 x 2 1/2 x 3/16	3.07	61.4
	1.92	38.4		1/4	4.10
				3/8	5.90
1 1/2 x 1 1/2 x 1/8	1.23	24.6			
	1.80	36.0	3 x 3 x 1/4	4.90	98.0
	2.34	46.8		3/8	7.20

Type 316

Hot Rolled, Annealed and Pickled
Stock Lengths, 19' to 21'

Size in Inches	Est. Weight, Lbs.		Size in Inches	Est. Weight, Lbs.	
	Per Foot	20 Ft. Length		Per Foot	20 Ft. Length
3/4 x 3/4 x 1/8	.59	11.8	1 1/2 x 1 1/2 x 1/4	2.34	46.8
1 x 1 x 1/8	.80	16.0			
	1.16	23.2	2 x 2 x 3/16	2.44	48.8
				1/4	3.19
1 1/4 x 1 1/4 x 1/8	1.01	20.2			
	1.48	29.6	2 1/2 x 2 1/2 x 3/16	3.07	61.4
	1.92	38.4		1/4	4.10
1 1/2 x 1 1/2 x 1/8	1.23	24.6		3/8	5.90
	1.80	36.0	3 x 3 x 1/4	4.90	98.0

STAINLESS STEEL TUBING WELDED Type 304 Type 316

Annealed White Pickled Finish
Polished Surfaces Available
Stock Lengths, 5' to 24' Random

O.D.	Wall Thickness			Estimated Wt. Lbs. Per Foot	O.D.	Wall Thickness			Estimated Wt. Lbs. Per Foot
	Ga.	Dec.	I.D.			Ga.	Dec.	I.D.	
3/8	21	.032	.311	.117	1 1/2	20	.035	1.430	.550
						18	.049	1.402	.759
1/2	20	.035	.430	.170	16	.065	1.370	1.00	
	16	.065	.370	.302	11	.120	1.260	1.77	
3/8	20	.035	.555	.220	1 1/4	16	.065	1.620	1.17
	18	.049	.527	.300					
	16	.065	.495	.388	2	20	.035	1.930	.73
3/4	20	.035	.680	.270	18	.049	1.902	1.02	
	18	.049	.652	.370	16	.065	1.870	1.34	
	16	.065	.620	.480	11	.120	1.760	2.41	
7/8	16	.065	.745	.560	2 1/2	16	.065	1.995	1.43
1	20	.035	.930	.360	2 1/2	18	.049	2.402	1.28
	18	.049	.902	.497	16	.065	2.370	1.69	
	16	.065	.870	.649	14	.083	2.334	2.14	
1 1/4	20	.035	1.180	.450	11	.120	2.260	3.05	
	18	.049	1.152	.630					
	16	.065	1.120	.823	3	16	.065	2.870	2.04
	14	.083	1.084	1.03	14	.083	2.834	2.59	
	11	.120	1.010	1.45	11	.120	2.760	3.69	
1 3/8	18	.049	1.277	.690	4	16	.065	3.870	2.73
					11	.120	3.760	4.97	

THINK TWICE
before you buy on price

Today's competition in the steel fabricating business is tougher than ever before. All the more reason to take the long view and think in terms of years rather than orders when evaluating your steel supply source. Our customers have long proved that, year in and year out, our prices are **always competitive**. We have enjoyed your business and are ever watchful for ways and means to serve you even better.

METAL SUPPLY INC.

800-400-6382 • sales@metalsupply.com



STAINLESS STEEL TUBING SEAMLESS Type 304 Type 316

Annealed White Pickled Finish
Polished Surfaces Available
Stock Lengths, 18' to 22' Random

O.D.	Wall Thickness			Estimated Wt. Lbs. Per Foot	O.D.	Wall Thickness			Estimated Wt. Lbs. Per Foot	
	Ga.	Dec.	I.D.			Ga.	Dec.	I.D.		
1/4	20	.035	.180	.0804	1 1/8	14	.083	.959	.9237	
	16	.065	.120	.1284		11	.120	.885	1.288	
5/16	20	.035	.243	.1039	1 1/4	18	.049	1.152	.628	
	18	.049	.215	.1382		16	.065	1.120	.822	
	16	.065	.183	.1722		13	.095	1.060	1.172	
3/8	20	.035	.305	.1271	1 1/2	11	.120	1.010	1.448	
	18	.049	.277	.1706		3/16	.188	.875	2.132	
	16	.065	.245	.2152		20	.035	1.430	.547	
7/16	20	.035	.368	.1506	16		.065	1.370	.996	
	18	.049	.340	.2036	14		.083	1.334	1.256	
1/2	20	.035	.430	.1738	1 3/4	18	.049	1.652	.890	
		.049	.402	.2360		16	.065	1.620	1.170	
		.065	.370	.3020		11	.120	1.510	2.089	
		.120	.260	.4870		3/16	.188	1.375	3.136	
5/8	20	.035	.493	.1974	2	20	.035	1.930	.734	
		.049	.465	.2690		18	.049	1.902	1.021	
		.065	.433	.3457		16	.065	1.870	1.343	
		.035	.555	.2205		14	.083	1.834	1.699	
3/4	18	.049	.527	.3014	2 1/4	12	.109	1.782	2.201	
		.065	.495	.3888		11	.120	1.760	2.409	
		.083	.459	.4805		3/16	.188	1.625	3.638	
		.035	.680	.2673		2 1/2	16	.065	2.120	1.517
.042	.666	.3176	13	.095	2.060		2.186			
.049	.652	.3668	11	.120	2.010		2.730			
.065	.620	.4755	3/16	.188	1.875		4.140			
7/8	13	.095	.560	.6646	3	1/4	.250	1.750	5.340	
		.120	.510	.8074		2 1/2	18	.049	2.402	1.283
		.035	.777	.4323			16	.065	2.370	1.690
		.049	.745	.5623			11	.120	2.260	3.050
.065	.745	.9676	3/16	.188	2.124		4.642			
1	11	.120	.635	.9676	3 1/4	1/4	.250	2.000	6.008	
		.035	.930	.3607		18	.065	2.870	2.037	
		.049	.902	.4977			14	.083	2.834	2.586
		.065	.870	.6491			13	.095	2.810	2.947
.083	.834	.8129	11	.120	2.760		3.691			
1 1/8	11	.120	.760	1.128	3 1/2	1/4	.250	2.500	7.343	
		.250	.500	2.003		11	.120	3.010	4.011	

STAINLESS STEEL PIPE WELDED I.P.S. Type 304 I.P.S. Type 316

Annealed White Pickled Finish
Polished Surfaces Available
Stock Lengths, 17' to 24' Random

Size in Inches	Wall Thickness			Estimated Wt. Lbs. Per Foot	Size in Inches	Wall Thickness			Estimated Wt. Lbs. Per Foot
	O.D.	I.D.	Wt. Thick.			O.D.	I.D.	Wt. Thick.	
1/8	.405	.269	.068	.244	1	1.315	1.049	.133	1.678
	.540	.364	.088	.424		1 1/4	1.660	1.380	.140
1/4	.675	.493	.091	.567	1 1/2	1.900	1.610	.145	2.717
	.840	.622	.109	.850		2	2.375	2.067	.154
3/4	1.050	.824	.113	1.130					

SEAMLESS I.P.S. Type 304 I.P.S. Type 316

Annealed White Pickled Finish
Polished Surfaces Available
Stock Lengths, 4' to 24' Random

Size in Inches	Wall Thickness			Estimated Wt. Lbs. Per Foot	Size in Inches	Wall Thickness			Estimated Wt. Lbs. Per Foot
	O.D.	I.D.	Wt. Thick.			O.D.	I.D.	Wt. Thick.	
STANDARD PIPE SIZES					EXTRA HEAVY PIPE SIZES				
1/8	.405	.269	.068	.244	1 1/8	1.315	.215	.095	.3145
1/4	.540	.364	.088	.424	1 1/4	1.660	.302	.119	.5351
3/8	.675	.493	.091	.567	3/8	.675	.423	.126	.7388
1/2	.840	.622	.109	.850	1/2	.840	.546	.147	1.088
3/4	1.050	.824	.113	1.130	3/4	1.050	.742	.154	1.474
1	1.315	1.049	.133	1.678	1	1.315	.957	.179	2.172
1 1/4	1.660	1.380	.140	2.272	1 1/4	1.660	1.278	.191	2.997
1 1/2	1.900	1.610	.145	2.717	1 1/2	1.900	1.500	.200	3.631
2	2.375	2.067	.154	3.652	2	2.375	1.939	.218	5.022
2 1/2	2.875	2.469	.203	5.793	2 1/2	2.875	2.323	.276	7.661
3	3.500	3.068	.216	7.575	3	3.500	2.900	.300	10.25
3 1/2	4.000	3.548	.226	9.109	3 1/2	4.000	3.364	.318	12.51
4	4.500	4.026	.237	10.79	4	4.500	3.826	.337	14.98
5	5.563	5.047	.258	14.62	5	5.563	4.813	.375	20.78
6	6.625	6.065	.280	18.97	6	6.625	5.761	.432	28.57
8	8.625	7.981	.322	28.55	8	8.625	7.625	.500	43.39

EXPERIENCE COUNTS when the heat's on

It's the men who serve you who make the difference. At our Steel Service Center, the combined experience of the men who receive and handle your orders adds up to hundreds of years. To see that you get top quality, the right alloy, the proper weight, size, shape, the optimum amount of pre-processing...these and many other split second decisions are made every day by the mental computers of our thoroughly experienced steel men. Result: you avoid costly production problems and slowdowns. Our experience and know-how is the plus factor you get in every pound of steel you buy from us.